

# VUSION LN-830E+



## TECHNICAL DETAILS

|                                 |  |
|---------------------------------|--|
| <b>Product code</b>             | LN-830E+ (WW): 63513<br>LN-830E+ (US): 63514                                       |
| <b>Dimensions (mm)</b>          | 205 x 42 x 205 mm  |
| <b>Housing</b>                  | Robust & modern synthetic housing, rear connectors                                 |
| <b>ESL Management</b>           | 10 000 labels  |
| <b>Coverage</b>                 | 20 000 sq ft (depending on shop layout)  |
| <b>Weight</b>                   | 640 g  |
| <b>Antennas</b>                 | Two Integrated Antennas  |
| <b>Power supply</b>             | 12 V DC, external power adapter (230 V) with bayonet connector, PoE (IEEE 802.3af) |
| <b>Power consumption (max.)</b> | 11 Watt on 12 V/1.5 A<br>12 Watt on PoE  |
| <b>Operating temperature</b>    | Temperature range 0 – 35°C; humidity 0 – 95%; non-condensing                       |
| <b>Compliance</b>               | CE, RoHS   |

## INTERFACES

|                               |  |
|-------------------------------|--|
| <b>ESL</b>                    | 10 000 labels  |
| <b>WLAN</b>                   | 2; Recommended if separate staff and public WiFi is necessary<br>2.4 GHz standarts: 802.11b/g/n<br>5 GHz standarts: 802.11a/n/ac |
| <b>iBeacon</b>                | Integrated iBeacon (standart 4.0 Bluetooth Low Energy)   |
| <b>Ethernet</b>               | 2 x 10/100/1000BASE-T Autosensing (RJ-45), IEEE 802.3az, PoE on ETH1   |
| <b>VLAN</b>                   | Yes  |
| <b>Centralized management</b> | Yes, but additional software is necessary (Large Scale Monitor from LANCOM) Q2-Q3/2017 via LANCOM Management Cloud               |