

VUSION

Retail IoT Connector

with USB cable and mounting bracket



TECHNICAL DETAILS

Model	APG2-USB1-A
Part references	CE: 7559 FCC/IC: 7561
Supported access points / firmware version	Cisco Catalyst C91xx / v17.3 or later Extreme Networks: AP 8432 / 5.9.2 or later LANCOM: LN-830U / 10.32 or later
V:IoT radio	2.4GHz
V:IoT radio protocol	proprietary
V:IoT radio antenna	pre-assembled hinged dipole SMA antenna
V:IoT radio channel auto-selection	Yes
Encryption	128-bit advanced encryption standard with secure key exchange
Coexistence (V:IoT radio + WiFi)	3m USB cable for antenna separation included
Transmission range:	25 meters indoors (about 1950m ² or 21000sq ft)
Labels supported	Up to 10000 per AP
Core Service compatibility	≥ 1.9.0
Compliance	FCC/IC, CE, RoHS
Power consumption	max. 0.25W
MOQ	1
Dimensions	170.5 x 25.4 x 12.7mm
Weight	0.025 kg
Temperature / Humidity	0°C to 40°C / 10% to 80% non-condensing

*For details see product specification

EXEMPLARY PICTURE



TECHNICAL DRAWINGS

